


# HRP-VX SERIE Drehbare Pulverisierer



| DREHBARE PULVERISIERER   |                           |       | HRP-4VX | HRP-7VX  | HRP-11VX | HRP-14VX  | HRP-18VX  | HRP-21VX  |
|--|---------------------------|-------|---------|----------|----------|-----------|-----------|-----------|
|   | Baggerklasse <sup>1</sup> | t     | 3 - 8   | 6 - 13   | 9 - 17   | 12 - 20   | 14 - 23   | 16 - 27   |
|   | Gewicht                   | kg    | 340     | 620      | 1100     | 1480      | 1780      | 2100      |
|   | Maulweite                 | mm    | 415     | 520      | 605      | 655       | 720       | 780       |
|   | Messerlänge               | mm    | 120     | 150      | 150      | 160       | 200       | 200       |
|   | Arbeitsdruck              | bar   | 280     | 320      | 320      | 350       | 350       | 350       |
|   | Ölvolumenstrom            | l/min | 30 - 70 | 60 - 100 | 70 - 110 | 110 - 160 | 140 - 200 | 180 - 230 |
|   | Arbeitsdruck rotieren     | bar   | 100     | 100      | 100      | 140       | 140       | 140       |
|   | Ölvolumenstrom rotieren   | l/min | 10 - 25 | 20 - 40  | 20 - 40  | 30 - 60   | 40 - 60   | 40 - 60   |
|  | Max. Durchmesser          | mm    | 28      | 30       | 30       | 40        | 40        | 50        |

| DREHBARE PULVERISIERER  |                           |       | HRP-24VX  | HRP-35VX  | HRP-45VX  | HRP-52VX  | HRP-72VX  |
|---|---------------------------|-------|-----------|-----------|-----------|-----------|-----------|
|  | Baggerklasse <sup>1</sup> | t     | 20 - 32   | 26 - 40   | 32 - 55   | 50 - 70   | 65 - 90   |
|  | Gewicht                   | kg    | 2480      | 3500      | 4400      | 4980      | 6870      |
|  | Maulweite                 | mm    | 880       | 1000      | 1100      | 1250      | 1400      |
|  | Messerlänge               | mm    | 200       | 200       | 250       | 250       | 250       |
|  | Arbeitsdruck              | bar   | 350       | 350       | 350       | 350       | 350       |
|  | Ölvolumenstrom            | l/min | 200 - 300 | 250 - 350 | 350 - 450 | 400 - 500 | 450 - 600 |
|  | Arbeitsdruck rotieren     | bar   | 140       | 140       | 140       | 140       | 140       |
|  | Ölvolumenstrom rotieren   | l/min | 40 - 60   | 40 - 60   | 40 - 60   | 40 - 60   | 50 - 70   |
|  | Max. Durchmesser          | mm    | 55        | 60        | 65        | 70        | 80        |

<sup>1</sup> Empfohlene Bagger / Anbauteil Kombination  
Ausgestattet mit austauschbaren Zähnen, Klingen und Platten

